



Features

- Sturdy and solid structure
- Insect proof pop-up swivel
- Wetted Diameter: 5.5-12mtr, 1.3-2.5 mtr with break away tab
- Discharge Flow Rates : 30 to 350 ltr/hr
- Operating Pressure Range : 1.0 to 3.0 kg/cm²
- Various Nozzle sizes gives variable range of discharge
- Unique water spreader for uniform distribution, maximum range and large droplets.
- Break away tab on two stage swivel to increase the wetted diameters from young to mature trees

Application

- For widely spaced plantation (upto 6m. X 6m. spacing) such as Ground Nut, Onions, Garlic, Mango, Walnut etc.
- Recommended for under tree and overhead irrigation.



Connection: Pushfit Type (Regular Swivel)

Swivel Color	Nozzle color	Nozzle (mm)	1.5 Kg/cm ²		2.0 Kg/cm ²		2.5 Kg/cm ²	
			Flow (lph)	Dia. (m)	Flow (lph)	Dia. (m)	Flow (lph)	Dia. (m)
 Black	Violet	0.8	28	5.5	36	6.0	41	6.2
	Brown	0.94	42	6.0	52	6.5	57	6.7
 Blue	Grey	1.14	62	7.2	71	8.0	80	8.2
	Green	1.4	90	8.2	102	8.4	118	8.5
 Green	Orange	1.5	105	8.5	122	9.0	136	9.4
	Black	1.78	140	9.0	162	9.4	180	9.8
	Blue	1.98	174	9.7	202	10.0	225	10.3
	Yellow	2.2	210	10.0	245	10.5	295	10.7
	Red	2.4	245	10.2	290	10.8	350	11.0

*Tested at 25cm height.

Swivels with Deflector - Wetted Diameter (m)

Nozzle color	Flow Rate (lph)	Nozzle Size (mm)	 Purple		 Grey	
			1 st stage	2 nd stage	1 st stage	2 nd stage
Black	71	1.14	1.3	3.2	1.9	4.8
Green	102	1.40	1.4	3.2	1.9	5.0
Orange	122	1.50	1.5	3.4	2.0	5.3
Black	162	1.78	1.6	3.5	2.0	5.4
Blue	202	1.98	1.6	4.0	2.2	6.0
Yellow	245	2.20	1.7	4.2	2.2	6.5
Red	290	2.40	1.8	4.5	2.5	6.8

*Tested at 25cm height.